7565 1K-PU
Adhesive Sealant

product information

AP-Merit 7565 1K-PU Adhesive & Sealant is a high-strength, fast moisture-curing 1K polyurethane. After curing, it remains flexible and adheres very well. Used in automotive, marine and construction/assembly applications for bonding PVC, wood, PC, PBTO, PU, concrete, glass and metal. Paintable, good UV resistance and does not shrink.

Color	grey, black and white
Drying	temperature 20°C
Skin formation Full cure	After 45 min. and at least 50% humidity 3 mm after 24 hours and min. 50% humidity
Temperature resistant	-40°C to +90°C (on cured sealant)
Overpaintable	Can be overpainted with most common paint systems. Pre-testing is recommended.
Bonding	The application quantity depends on the type and nature of the material to be bonded. Apply and press down within 10 minutes.

Notes:

Surfaces should be clean, dust-free, grease-free and dry.
The surface temperature should be 12 to 25°C

Material can still be reshaped after a short curing time, e.g.: finger, japenese putty spreader set etc.

Processing conditions:
min. +5°C and + 25°C

Storage and shelf life:
Store the product in a ventilated place. Protect from direct sunlight. Store between +5°C and 25°C. Shelf life at least 12 months.

Processing equipment:
AP-Merit cartridge gun premium No: 75465 with a force ratio of 12:1

This product sheet is for information purposes only ! To the best of our knowledge, the information given here corresponds to the state of the art and is based on many years of experience in the manufacture of our products. However, the information is nonbinding and without guarantee.