Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: AP-Merit Unterbodenschutz Bitumen Spray**
· **UFI:** DX20-K0FY-8005-AN8S
· **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
· **Application of the substance / the mixture** Protective coating

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Wolfgang GesmbH
Barnabas-Fink-Str. 11
A-6845 Hohenems
Tel : +43 (0) 5576 / 72330
eMail: office@ap-merit.com
· **1.4 Emergency telephone number:** Vergiftungsinformationszentrale Wien +43 (0)1 4064343

*

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Xylene
· **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 1)

· ***Precautionary statements***

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· ***Additional information:***
Buildup of explosive mixtures possible without sufficient ventilation.
· ***2.3 Other hazards***
· ***Results of PBT and vPvB assessment***
· ***PBT:*** Not applicable.
· ***vPvB:*** Not applicable.

*

SECTION 3: Composition/information on ingredients

· ***3.2 Chemical characterisation: Mixtures***
· ***Description:*** Mixture of substances listed below with nonhazardous additions.

· ***Dangerous components:***

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-≤20%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%

· ***Additional information:*** For the wording of the listed hazard phrases refer to section 16.

*

SECTION 4: First aid measures

· ***4.1 Description of first aid measures***
· ***General information:*** Immediately remove any clothing soiled by the product.
· ***After inhalation:*** Supply fresh air; consult doctor in case of complaints.
· ***After skin contact:*** Immediately rinse with water.
· ***After eye contact:*** Rinse opened eye for several minutes under running water.
· ***After swallowing:*** Seek immediate medical advice.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 2)

· ***4.3 Indication of any immediate medical attention and special treatment needed***
No further relevant information available.

*
SECTION 5: Firefighting measures

· ***5.1 Extinguishing media***
· ***Suitable extinguishing agents:***
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· ***5.2 Special hazards arising from the substance or mixture***
During heating or in case of fire poisonous gases are produced.
· ***5.3 Advice for firefighters***
· ***Protective equipment:***
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

*
SECTION 6: Accidental release measures

· ***6.1 Personal precautions, protective equipment and emergency procedures***
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· ***6.2 Environmental precautions:*** *Do not allow to enter sewers/ surface or ground water.*
· ***6.3 Methods and material for containment and cleaning up:***
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
· ***6.4 Reference to other sections***
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

· ***7.1 Precautions for safe handling***
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
· ***Information about fire - and explosion protection:***
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· ***7.2 Conditions for safe storage, including any incompatibilities***
· ***Storage:***
· ***Requirements to be met by storerooms and receptacles:***
Observe official regulations on storing packagings with pressurised containers.
· ***Information about storage in one common storage facility:*** *Store away from foodstuffs.*
· ***Further information about storage conditions:***
Do not seal receptacle gas tight.
Keep container tightly sealed.
· ***Storage class:*** *2 B*
· ***7.3 Specific end use(s)*** *No further relevant information available.*

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 3)

*

SECTION 8: Exposure controls/personal protection

· ***8.1 Control parameters***

· ***Additional information about design of technical facilities:*** *No further data; see item 7.*

· ***Ingredients with limit values that require monitoring at the workplace:***	
115-10-6 dimethyl ether	
WEL	*Short-term value: 958 mg/m³, 500 ppm* *Long-term value: 766 mg/m³, 400 ppm*
1330-20-7 Xylene	
WEL	*Short-term value: 441 mg/m³, 100 ppm* *Long-term value: 220 mg/m³, 50 ppm* *Sk; BMGV*
100-41-4 Ethylbenzene	
WEL	*Short-term value: 552 mg/m³, 125 ppm* *Long-term value: 441 mg/m³, 100 ppm* *Sk*

· ***Ingredients with biological limit values:***	
1330-20-7 Xylene	
BMGV	*650 mmol/mol creatinine* *Medium: urine* *Sampling time: post shift* *Parameter: methyl hippuric acid*

· ***Additional information:*** *The lists valid during the making were used as basis.*

· ***8.2 Exposure controls***

· ***Personal protective equipment:***

· ***General protective and hygienic measures:***

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· ***Respiratory protection:***

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· ***Protection of hands:***

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· ***Material of gloves***

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 4)

· ***Breakthrough time of glove material***
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· ***Eye protection:***
Safety glasses

Tightly sealed goggles

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Aerosol
Colour:	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-24.9 °C
· **Flash point:**	<0 °C (DIN 53213)
· **Flammability (solid, gas):**	Not applicable.
· **Ignition temperature:**	287 °C (DIN 51794)
· **Decomposition temperature:**	Not determined.
· **Auto-ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Explosion limits:**	
Lower:	1.1 Vol %
Upper:	18.6 Vol %
· **Vapour pressure at 20 °C:**	5,200 hPa
· **Density at 20 °C:**	1.029 g/cm³ (DIN 53217)
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Water:	0.0 %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 5)

VOC (EC)	*50.70 %*
Solids content (weight-%):	*49.3 %*
· ***9.2 Other information***	*No further relevant information available.*

*

SECTION 10: Stability and reactivity

· ***10.1 Reactivity*** *No further relevant information available.*
· ***10.2 Chemical stability***
· ***Thermal decomposition / conditions to be avoided:*** *No decomposition if used according to specifications.*
· ***10.3 Possibility of hazardous reactions*** *No dangerous reactions known.*
· ***10.4 Conditions to avoid*** *No further relevant information available.*
· ***10.5 Incompatible materials:*** *No further relevant information available.*
· ***10.6 Hazardous decomposition products:*** *Carbon monoxide*

*

SECTION 11: Toxicological information

· ***11.1 Information on toxicological effects***
· ***Acute toxicity*** *Based on available data, the classification criteria are not met.*
· ***Primary irritant effect:***
· ***Skin corrosion/irritation***
Causes skin irritation.
· ***Serious eye damage/irritation***
Causes serious eye irritation.
· ***Respiratory or skin sensitisation*** *Based on available data, the classification criteria are not met.*
· ***Additional toxicological information:***
· ***CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)***
· ***Germ cell mutagenicity*** *Based on available data, the classification criteria are not met.*
· ***Carcinogenicity*** *Based on available data, the classification criteria are not met.*
· ***Reproductive toxicity*** *Based on available data, the classification criteria are not met.*
· ***STOT-single exposure*** *Based on available data, the classification criteria are not met.*
· ***STOT-repeated exposure***
May cause damage to organs through prolonged or repeated exposure.
· ***Aspiration hazard***
May be fatal if swallowed and enters airways.

*

SECTION 12: Ecological information

· ***12.1 Toxicity***
· ***Aquatic toxicity:*** *No further relevant information available.*
· ***12.2 Persistence and degradability*** *No further relevant information available.*
· ***12.3 Bioaccumulative potential*** *No further relevant information available.*
· ***12.4 Mobility in soil*** *No further relevant information available.*
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· ***12.5 Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable.*
· ***vPvB:*** *Not applicable.*

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 6)

· ***12.6 Other adverse effects*** *No further relevant information available.*

*
SECTION 13: Disposal considerations

· ***13.1 Waste treatment methods***
· ***Recommendation***
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· ***Uncleaned packaging:***
· ***Recommendation:*** *Disposal must be made according to official regulations.*

*
SECTION 14: Transport information

· ***14.1 UN-Number***	
· ***ADR, IMDG, IATA***	*UN1950*
· ***14.2 UN proper shipping name***	
· ***ADR***	*UN1950 AEROSOLS*
· ***IMDG***	*AEROSOLS (Naphtha, aliphatic, Hydrocarbons, C7), MARINE POLLUTANT*
· ***IATA***	*AEROSOLS, flammable*
· ***14.3 Transport hazard class(es)***	
· ***ADR***	
· ***Class***	*2 5F Gases.*
· ***Label***	*2.1*
· ***IMDG***	
· ***Class***	*2.1 Gases.*
· ***Label***	*2.1*
· ***IATA***	
· ***Class***	*2.1 Gases.*
· ***Label***	*2.1*
· ***14.4 Packing group***	
· ***ADR, IMDG, IATA***	*Void*
· ***14.5 Environmental hazards:***	*Product contains environmentally hazardous substances: Naphtha, aliphatic*
· ***Marine pollutant:***	*Yes* *Symbol (fish and tree)*
· ***14.6 Special precautions for user***	*Warning: Gases.*

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 7)

· ***Hazard identification number (Kemler code):***	-
· ***EMS Number:***	*F-D,S-U*
· ***Stowage Code***	*SW1 Protected from sources of heat.* *SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.*
· ***Segregation Code***	*SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.* *For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.* *For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.*
· ***14.7 Transport in bulk according to Annex II of Marpol and the IBC Code***	*Not applicable.*
· ***Transport/Additional information:***	
· ***ADR***	
· ***Limited quantities (LQ)***	*1L*
· ***Transport category***	*2*
· ***Tunnel restriction code***	*D*
· ***IMDG***	
· ***Limited quantities (LQ)***	*1L*
· ***UN "Model Regulation":***	*UN 1950 AEROSOLS, 2.1*

*

SECTION 15: Regulatory information

· ***15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture***

· ***Directive 2012/18/EU***
· ***Named dangerous substances - ANNEX I*** *None of the ingredients is listed.*
· ***Seveso category*** *P3a FLAMMABLE AEROSOLS*
· ***Qualifying quantity (tonnes) for the application of lower-tier requirements*** *150 t*
· ***Qualifying quantity (tonnes) for the application of upper-tier requirements*** *500 t*

· ***National regulations:***
· ***Additional classification according to Decree on Hazardous Materials, Annex II:***

Class	*Share in %*
NK	*50-100*

· ***15.2 Chemical safety assessment:*** *A Chemical Safety Assessment has not been carried out.*

*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· ***Relevant phrases***
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.06.2022 *Version number 3* *Revision: 22.06.2022*

Trade name: AP-Merit Unterbodenschutz Bitumen Spray

(Contd. of page 8)

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· ***Classification according to Regulation (EC) No 1272/2008***
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· ***Abbreviations and acronyms:***
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Liq.): Gases under pressure – Liquefied gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **** Data compared to the previous version altered.***